



## Modification of Polysulfone for Proton Exchange Membranes

Nielsen, Mads Møller; Dimitrov, Ivaylo; Takamuku, Shogo; Jannasch, Patric; Jankova Atanasova, Katja; Hvilsted, Søren

*Publication date:*  
2011

[Link back to DTU Orbit](#)

*Citation (APA):*

Nielsen, M. M., Dimitrov, I., Takamuku, S., Jannasch, P., Jankova Atanasova, K., & Hvilsted, S. (2011). *Modification of Polysulfone for Proton Exchange Membranes*. Poster session presented at EPF 5th summer school: Fundamentals and Developments in Polymer Processing Science and Technology, Gargnano, Italy.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.


# Modification of Polysulfone for Proton Exchange Membranes

*Mads M. Nielsen<sup>1</sup>, Ivaylo Dimitrov<sup>1</sup>, Shogo Takamuku<sup>2</sup>, Patric Jannasch<sup>2</sup>,  
Katja Jankova<sup>1</sup>, Søren Hvilsted<sup>1</sup>*

<sup>1</sup>*Department of Chemical and Biochemical Engineering, Danish Polymer Centre, Technical University of Denmark,  
Soltofts Plads 227, DK-2800 Kgs. Lyngby, Denmark*

<sup>2</sup>*Division of Polymer and Materials Chemistry, Lund University, P. O. Box 124, SE-221 00 Lund, Sweden  
mon@kt.dtu.dk; Tel.: +45 4525 6817; Fax: +45 4588 2161*

The main hurdles on the field of Proton Exchange Membranes (PEM) in fuel cells (FC) are to obtain better durability, and improved performance at >80 °C at a reduced cost<sup>1</sup>. The proton conductivity of state-of-the-art perfluorosulfonic acid (PFSA) type membranes like Nafion® generally decays at higher temperatures, where the PEMFC system is more beneficial<sup>2</sup>. An alternative backbone is the commercially polysulfone (PSU) Udel® with good chemical, thermal and mechanical as well as film forming properties - the latter is a feature that easily rules otherwise strong candidates out<sup>3</sup>. Introduction of sulfonic acid groups in PSU is performed by “click” chemistry or through grafting by Atom Transfer Radical Polymerization (ATRP) from a short spacer, expected to contribute to the segregation onto hydrophobic and hydrophilic domains. By combination of well defined precursor backbones with the quantitative “click” chemistry and the controlled ATRP the Ion Exchange Capacity (IEC) can be tuned.



**Figure 1.** The pursued ways to modify the PSU backbone: “clicking” two different small molecules onto the backbone at the same number of sites, (a-b) or at a different amount of sites (c) - or by ATRP of the same monomer to different chain lengths (d-e) and from a different macroinitiator (f).

## References:

<sup>1</sup> Y. Wang, K. S. Chen, J. Mishler, S. C. Cho, X. C. Adroher *Appl. Energ.* **88** (2011) 981-1007

<sup>2</sup> J. A. Mader, B. C. Benicewicz *Macromolecules* **43** (2010) 6706-6715

<sup>3</sup> I. Dimitrov, K. Jankova, S. Hvilsted *J. Polym. Sci. Part A: Polym. Chem* **46** (2008) 7827-7834; **48** (2010) 2044-2052